Pump capacity
System relief at quick couplers

Max. travel speed

**Engine** 

Make / Model Fuel / Cooling

Max power @ 3000 RPM (SAE J1349) Torque at 2200 RPM (SAE J1349) Number of cylinders Displacement

Fuel tank capacity

Weights Operating weight

Controls

Vehicle steering Loader hydraulics tilt and lift

Front auxiliary

**Drive System** 

Transmission

**Standard Features** 

Automatically activated glow plugs Bob-Tach™ frame Bobcat Interlock Control System (BICS)

Engine / Hydraulic system shutdown Front auxiliary hydraulics High-back cushion suspension seat

Instrumentation

Lift arm support
23 x 5.70-12, 4–ply, Narrow tyres
Operating lights, front and rear
Operator cab\*

Parking brake
\*Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471

**Options** 

Heated enclosed cab

23 x 8.50-12, 6-ply, Heavy duty tyres

686 kg

207 bar

9.8 km/h

16.8 kW 62.8 Nm

1001 cm<sup>3</sup>

1268 kg

Separate foot pedals

Rear and top window Seat belt Seat bar

Spark arrestor muffler CE certification


24.61

Diesel / Liquid

37 l/min @ 100% efficiency

Kubota / D1005-E3B-BC-3

## **Dimensions**



(A)	3131 mm
(B)	1830 mm
C)	25°
D)	141 mm
E)	722 mm
(F)	1917 mm
(G)	2553 mm
H)	22°
(1)	1891 mm

Direction and speed controlled by two hand levers

Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors

Lateral movement of right-hand steering lever

(J)	2399 mm
(K)	469 mm
(L)	34°
(M)	97°
(N)	1175mm
(0)	1557 mm
(P)	752 mm
ini	1110 mm



betterrentals.com.au

03 59966 088 Cranbourne Pakenham 03 5941 2299 Mornington 03 5977 0770 Ferntree Gully 03 0759 8444 Carrum Downs 03 5973 4403

ww.bobcat.eu

